

SECTION 015800

PROJECT IDENTIFICATION AND SIGNS

PART 1 GENERAL

1.1 DESCRIPTION OF WORK

Requirements include the following which shall be provided by the Contractor for General Construction:

- A. Furnish, install and maintain project identification sign.
- B. Provide temporary on-site information signs to identify Owner's temporary relocation.
- C. Remove signs on completion of construction.
- D. Allow no other signs to be displayed without approval of owner.

1.2 RELATED REQUIREMENTS

- A. Section 011100 – Summary of Work
- B. Section 015000 – Temporary Facilities and Controls
- C. Section 0151719 – Environmental Controls

1.3 PROJECT IDENTIFICATION SIGN

- A. Two (2) painted signs, not less than 4 feet x 8 feet, with painted graphic content as shown on sample exhibit attached on page 3 of this section.
- B. Erect on the site at location shown on drawing or as directed by the owner.

1.4 INFORMATIONAL SIGNS

- A. Provide at all public entrances, stairways and temporary gates painted signs with painted lettering indicating Owner's relocated address. Each sign to be 3 feet by 3 feet with up to 100 letters. Allow for a total of eight [8] signs.
- B. Erect at appropriate locations to provide required information. Coordinate location with owner/owner's representative.

1.5 QUALITY ASSURANCE

- A. Sign Painter: Professional experience in type of work required.
- B. Finishes, Painting: Adequate to resist weathering and fading for scheduled construction period.

PART 2 PRODUCTS

2.1 SIGN MATERIALS

- A. Structure and framing: May be new or used, wood or metal, in sound condition structurally adequate to work and suitable for specified finish.
- B. Sign surfaces: Exterior softwood plywood with medium density overlay, standard large sizes to minimize joints.
 - 1. Thickness: As required by standards to span framing members (not less than $\frac{3}{4}$ inch thick), to provide even, smooth surface without knots, waves or buckles.
- C. Rough hardware: Galvanized.
- D. Paint: Manufacturer's Best Exterior quality as approved by architect.
 - 1. Use exhibit for colors and graphics.
 - 2. Colors for structure, framing, sign surfaces and graphics: As selected by Architect.

PART 3 EXECUTION

3.1 PROJECT IDENTIFICATION SIGN

- A. Paint exposed surfaces of supports, framing and surface material; one coat of primer and one coat of exterior paint.
- B. Paint graphics in style, sizes and colors shown on exhibit attached on page 4 of this section.

3.2 INFORMATION SIGNS

- A. Paint exposed surfaces: One coat of primer and one coat of exterior paint.
- B. Paint graphics in style, sizes and colors selected by the architect.
- C. Install at a height for optimum visibility, on ground-mounted poles or attached to temporary structural surfaces.

3.3 MAINTENANCE

- A. Maintain signs and supports in a neat, clean condition; repair damages to structure, framing or sign.
- B. Relocate informational signs as required by progress of work.


3.4 REMOVAL

- A. Remove signs, framing, supports and foundations at completion of project.

END OF SECTION

NOTE:
ALL LETTERING ON BLUE FIELD
SHALL BE YELLOW

NOTE:
ALL LETTERING ON YELLOW FIELD
SHALL BE BLUE



NOTE:
CITY SEAL SHALL BE BLUE
ON YELLOW FIELD

SPECIFICATIONS FOR SIGNS

THIS SIGN MAY BE MADE OF WOOD OR METAL. IF WOOD IS TO BE USED THE SIGN FACE SHALL BE 3/4" GLUED EXTERIOR GRADE PLW'OOD, REINFORCED WITH FOUR (4) BATTENS 2"x4" EQUALLED SPACED. TOP AND BOTTOM RAILS TO BE 2"x4", SURFACED FOUR (4) SIDES AND SCREWED TO THE FACE BOARD ON 12" CENTERS. IF METAL IS TO BE USED, THE SIGN SHALL BE GALVANIZED STEEL, 24 GAUGE, LAPPED AND SECURED ON ALL SIDES.

BLOCK TYPE LETTERING TO BE USED

PAINT

1. BLUE-M.A.BRUDERS RUST-O-LASTIC 074-508 *PRECAUTION BLUE* DR EQUAL
2. YELLOW-M.A.BRUDERS RUST-O-LASTIC 074-326 *CAUTION YELLOW* DR EQUAL